



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 :

H01L 21/00

A1

(11) International Publication Number:

WO 00/54310

(43) International Publication Date: 14 September 2000 (14.09.00)

(21) International Application Number: PCT/NL00/00154

(22) International Filing Date: 8 March 2000 (08.03.00)

(30) Priority Data:

1011487

8 March 1999 (08.03.99)

NL

(71) Applicants (for all designated States except US): ASM INTERNATIONAL N.V. [NL/NL]; P.O. Box 100, NL-3720 AC Bilthoven (NL). KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-4521 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KUZNETSOV, Vladimir, Ivanovich [NL/NL]; Buenos Airesstraat 8, NL-2622 AX Delft (NL). RADELAAR, Sijbrand [NL/NL]; Soestdijkseweg 378, NL-3723 HK Bilthoven (NL). VAN DER SANDEN, Jacobus, Cornelis, Gerardus [NL/NL]; Zomerland 42, NL-5663 HV Geldrop (NL). RUIJL, Theo, Anjes, Maria [NL/NL]; Vleugendaal 64, NL-6351 HE Bochooltz (NL).

(74) Agent: JORRITSMA, Ruurd; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: METHOD AND DEVICE FOR ROTATING A WAFER

(57) Abstract

Method and device for rotating a wafer which is arranged floating in a reactor. The wafer is treated in a reactor of this nature, and it is important for this treatment to be carried out as uniformly as possible. For this purpose, it is proposed to rotate the wafer by allowing the gas flow to emerge perpendicular to the surface of the wafer and then to impart to this gas a component which is tangential with respect to the wafer, thus generating rotation. This tangential component may be generated by the provision of grooves, which may be of spiral or circular design.

